

SIMART 简灵科技



• 极佳的减震性

104系列
壁厚且耐用

• 承受边缘压力


• 抗冲击力

1

104系列·产品规格

简灵科技工程塑料轴承
High Wear Resistance. Cost Down.

轴套- S型(mm)



倒角f和内径d的关系:

d	Φ1-6	Φ6-12	Φ12-30	Φ>30
f	0.3	0.5	0.8	1.2

注: "当产品壁厚小于1mm时, 倒角为20°。
尺寸符合ISO 3547-1标准, 且提供定制服务。

订购编号示例

1 产品代码 104SM-0305-04

2 内径d 03

3 外径D 05

4 长度L 04

1 产品代码	2 d	d 公差	3 D	4 L
		压入 H7 孔后		
104SM-0103-02	1.0	+0.020 +0.080	3	2
104SM-0104-02	1.5		4	2
104SM-0205-01	2.0		5	1
104SM-0205-02	2.0		5	2
104SM-0205-03	2.0		5	3
104SM-0206-03	2.5		6	3
104SM-0305-03	3.0		5	3
104SM-0305-04	3.0		5	4
104SM-0306-03	3.0		6	3
104SM-0306-04	3.0		6	4
104SM-0405-04	4.0	+0.030 +0.105	5.5	4
104SM-0405-06	4.0		5.5	6
104SM-0407-03	4.0		7	3
104SM-0407-04	4.0		7	4
104SM-0407-06	4.0		7	6
104SM-0408-04	4.0		8	4
104SM-0408-06	4.0		8	6
104SM-0507-05	5.0		7	5
104SM-0507-10	5.0		7	10
104SM-0508-04	5.0		8	4
104SM-0508-05	5.0	+0.040 +0.130	8	5
104SM-0508-08	5.0		8	8
104SM-0509-05	5.0		9	5
104SM-0509-08	5.0		9	8
104SM-0608-06	6.0		8	6
104SM-0608-08	6.0		8	8
104SM-0608-10	6.0		8	10
104SM-0609-06	6.0		9	6
104SM-0610-02	6.0		10	2.5
104SM-0610-04	6.0		10	4
104SM-0610-06	6.0	+0.040 +0.130	10	6
104SM-0610-08	6.0		10	8
104SM-0610-10	6.0		10	10
104SM-0611-04	6.0		11	4
104SM-0612-06	6.0		12	6
104SM-0612-10	6.0		12	10
104SM-0710-05	7.0		10	5
104SM-0710-08	7.0		10	8
104SM-0710-10	7.0		10	10
104SM-0711-16	7.0		11	16
104SM-0810-06	8.0		10	6

1 产品代码	2 d	d 公差	3 D	4 L
		压入H7孔后		
104SM-0810-08	8.0	+0.040 +0.130	10	8
104SM-0810-10	8.0		10	10
104SM-0810-12	8.0		10	12
104SM-0811-06	8.0		11	6
104SM-0811-08	8.0		11	8
104SM-0811-12	8.0		11	12
104SM-0812-04	8.0		12	4
104SM-0812-06	8.0		12	6
104SM-0812-08	8.0		12	8
104SM-0812-10	8.0		12	10
104SM-0812-12	8.0	+0.050 +0.160	12	12
104SM-0814-06	8.0		14	6
104SM-0814-10	8.0		14	10
104SM-0912-14	9.0		12	14
104SM-1012-08	10		12	8
104SM-1012-10	10		12	10
104SM-1012-12	10		12	12
104SM-1012-15	10		12	15
104SM-1012-20	10		12	20
104SM-1014-06	10		14	6
104SM-1014-08	10	+0.050 +0.160	14	8
104SM-1014-10	10		14	10
104SM-1014-16	10		14	16
104SM-1016-06	10		16	6
104SM-1016-08	10		16	8
104SM-1016-10	10		16	10
104SM-1016-16	10		16	16
104SM-1016-50	10		16	50
104SM-1214-10	12		14	10
104SM-1214-12	12		14	12
104SM-1214-15	12	+0.050 +0.160	14	15
104SM-1214-20	12		14	20
104SM-1216-15	12		16	15
104SM-1216-20	12		16	20
104SM-1218-08	12		18	8
104SM-1218-10	12		18	10
104SM-1218-15	12		18	15
104SM-1218-20	12		18	20
104SM-1315-10	13		15	10
104SM-1315-20	13		15	20
104SM-1416-085	14		16	8.5

104系列壁厚
且耐用

104系列·产品规格

简灵科技工程塑料轴承
High Wear Resistance. Cost Down.



轴套- S型(mm)

1 产品代码	2 d	d 公差	3 D	4 L
		压入 H7 孔后		
104SM-1416-10	14	+0.050 +0.160	16	10
104SM-1416-15	14		16	15
104SM-1416-20	14		16	20
104SM-1416-25	14		16	25
104SM-1416-29	14		16	29
104SM-1418-20	14		18	20
104SM-1420-10	14		20	10
104SM-1420-15	14		20	15
104SM-1420-20	14		20	20
104SM-1517-10	15		17	10
104SM-1517-15	15		17	15
104SM-1517-20	15		17	20
104SM-1517-25	15		17	25
104SM-1521-10	15		21	10
104SM-1521-15	15		21	15
104SM-1521-20	15		21	20
104SM-1521-23	15		21	23
104SM-1618-12	16		18	12
104SM-1618-15	16		18	15
104SM-1618-20	16		18	20
104SM-1618-25	16		18	25
104SM-1620-20	16		20	20
104SM-1620-25	16		20	25
104SM-1620-30	16		20	30
104SM-1621-07	16		21	7
104SM-1622-12	16		22	12
104SM-1622-15	16		22	15
104SM-1622-16	16		22	16
104SM-1622-20	16		22	20
104SM-1622-25	16		22	25
104SM-1820-15	18		20	15
104SM-1820-20	18		20	20
104SM-1820-25	18		20	25
104SM-1824-12	18		24	12
104SM-1824-20	18		24	20
104SM-1824-30	18		24	30
104SM-1824-40	18		24	40
104SM-2023-10	20	+0.065 +0.195	23	10
104SM-2023-15	20		23	15
104SM-2023-20	20		23	20
104SM-2023-25	20		23	25
104SM-2023-30	20		23	30
104SM-2025-14	20		25	14
104SM-2025-20	20		25	20
104SM-2025-30	20		25	30
104SM-2026-12	20		26	12
104SM-2026-15	20		26	15
104SM-2026-20	20		26	20
104SM-2026-30	20		26	30
104SM-2224-08	22		24	8
104SM-2225-15	22		25	15
104SM-2225-20	22		25	20
104SM-2225-25	22		25	25
104SM-2225-30	22		25	30

1 产品代码	2 d	d 公差	3 D	4 L
		压入H7孔后		
104SM-2226-15	22	+0.065 +0.195	26	15
104SM-2228-10	22		28	10
104SM-2228-15	22		28	15
104SM-2228-20	22		28	20
104SM-2228-30	22		28	30
104SM-2427-15	24		27	15
104SM-2427-20	24		27	20
104SM-2427-25	24		27	25
104SM-2427-30	24		27	30
104SM-2430-15	24		30	15
104SM-2430-20	24		30	20
104SM-2430-30	24		30	30
104SM-2528-12	25		28	12
104SM-2528-15	25		28	15
104SM-2528-20	25		28	20
104SM-2528-25	25		28	25
104SM-2528-30	25		28	30
104SM-2530-20	25		30	20
104SM-2530-30	25		30	30
104SM-2530-40	25		30	40
104SM-2532-10	25		32	10
104SM-2532-12	25		32	12
104SM-2532-20	25		32	20
104SM-2532-30	25		32	30
104SM-2532-35	25		32	35
104SM-2532-40	25		32	40
104SM-2630-20	26		30	20
104SM-2632-30	26		32	30
104SM-2734-20	27		34	20
104SM-2734-30	27		34	30
104SM-2734-40	27		34	40
104SM-2832-20	28		32	20
104SM-2832-25	28		32	25
104SM-2832-30	28		32	30
104SM-2833-20	28		33	20
104SM-2836-20	28		36	20
104SM-2836-30	28		36	30
104SM-2836-40	28		36	40
104SM-3034-20	30	+0.032 +0.102	34	20
104SM-3034-25	30		34	25
104SM-3034-30	30		34	30
104SM-3034-40	30	+0.065 +0.195	34	40
104SM-3035-20	30		35	20
104SM-3035-40	30		35	40
104SM-3038-03	30	+0.080 +0.240	38	3.0
104SM-3038-045	30		38	4.5
104SM-3038-17	30		38	17
104SM-3038-20	30	+0.065 +0.195	38	20
104SM-3038-30	30		38	30
104SM-3038-40	30		38	40
104SM-3040-40	30		40	40

104系列壁厚
且耐用

104系列·产品规格

简灵科技工程塑料轴承
High Wear Resistance. Cost Down.



轴套- S型(mm)

1 产品代码	2 d	d 公差	3 D	4 L
		压入 H7 孔后		
104SM-3236-20	32	+0.080 +0.240	36	20
104SM-3236-30	32		36	30
104SM-3236-40	32		36	40
104SM-3240-20	32		40	20
104SM-3240-30	32		40	30
104SM-3240-40	32		40	40
104SM-3539-20	35		39	20
104SM-3539-30	35		39	30
104SM-3539-40	35		39	40
104SM-3539-50	35		39	50
104SM-3542-50	35		42	50
104SM-4044-20	40		44	20
104SM-4044-30	40		44	30
104SM-4044-40	40		44	40


1 产品代码	2 d	d 公差	3 D	4 L
		压入H7孔后		
104SM-4044-50	40	+0.080 +0.240	44	50
104SM-4046-20	40		46	20
104SM-4550-20	45		50	20
104SM-4550-30	45		50	30
104SM-4550-40	45		50	40
104SM-4550-50	45		50	50
104SM-5055-20	50		55	20
104SM-5055-30	50		55	30
104SM-5055-40	50		55	40
104SM-5055-50	50		55	50
104SM-5055-60	50		55	60
104SM-7580-60	75	+0.100 +0.290	80	60

104系列壁厚
且耐用

104系列·产品规格

简灵科技工程塑料轴承
High Wear Resistance. Cost Down.

法兰轴承- F型(mm)



倒角f和内径d的关系:

d	Φ1-6	Φ6-12	Φ12-30	Φ>30
f	0.3	0.5	0.8	1.2

注: "当产品壁厚小于1mm时, 倒角为20°。
尺寸符合ISO 3547-1标准, 且提供定制服务。

订购编号示例

1 产品代码 104FM-0408-04

2 内径d 04

3 外径D 08

4 长度L1 04

1 产品代码	2 d	d 公差 压入 H7 孔后	3 D1	D2	4 L1	L2
			d13	h13	-0.14	
104FM-0103-02	1	+0.020 +0.080	3	5	2	1
104FM-0104-02	1.5		4	6	2	1
104FM-0205-03	2		5	8	3	1.5
104FM-0206-03	2.5		6	9	3	1.5
104FM-0306-04	3	+0.030 +0.105	6	9	4	1.5
104FM-0408-04	4		8	12	4	2
104FM-0408-06	4		8	12	6	2
104FM-0408-08	4		8	12	8	2
104FM-0509-05	5		9	13	5	2
104FM-0509-06	5		9	13	6	2
104FM-0509-08	5		9	13	8	2
104FM-0608-04	6		8	12	4	1
104FM-0608-08	6		8	12	8	1
104FM-0610-04	6		10	14	4	2
104FM-0610-06	6		10	14	6	2
104FM-0610-10	6		10	14	10	2
104FM-0611-04	6		11	14	4	2
104FM-0612-06	6		12	14	6	3
104FM-0612-10	6		12	14	10	3
104FM-0711-06	7	+0.040 +0.130	11	15	6	2
104FM-0711-08	7		11	15	8	2
104FM-0809-055	8		9	13	5.5	0.5
104FM-0810-05	8		10	15	5.5	1
104FM-0810-07	8		10	15	7.5	1
104FM-0810-09	8		10	15	9.5	1
104FM-0811-05	8		11	13	5	2
104FM-0811-08	8		11	13	8	2
104FM-0812-06	8		12	16	6	2
104FM-0812-08	8		12	16	8	2
104FM-0812-12	8		12	16	12	2
104FM-0814-06	8		14	18	6	3
104FM-081416-06	8		14	16	6	3
104FM-0814-10	8		14	18	10	3
104FM-081416-10	8		14	16	10	3
104FM-0914-06	9	+0.050 +0.160	14	19	6	2
104FM-0914-10	9		14	19	10	2
104FM-0914-14	9		14	19	14	2
104FM-1012-07	10		12	18	7	1
104FM-1012-09	10		12	18	9	1
104FM-1014-09	10		12	18	9	1
104FM-1012-12	10		12	18	12	1

1 产品代码	2 d	d 公差 压入 H7 孔后	3 D1	D2	4 L1	L2
			d13	h13	-0.14	
104FM-1012-17	10	+0.040 +0.130	12	18	17	1
104FM-101419-08	10		14	19	8	2
104FM-1014-10	10		14	19	10	2
104FM-101419-12	10		14	19	12	1.5
104FM-101420-12	10		14	20	12	2
104FM-1014-14	10		14	17.5	14	1
104FM-1014-19	10		14	17.5	19	1
104FM-1014-24	10		14	17.5	24	1
104FM-1014-34	10		14	17.5	34	1
104FM-101620-06	10		16	20	6	3
104FM-1016-08	10		16	22	8	3
104FM-1016-10	10		16	22	10	3
104FM-101620-10	10		16	20	10	3
104FM-1016-16	10		16	22	16	3
104FM-1214-07	12		14	20	7	1
104FM-1214-09	12		14	20	9	1
104FM-1214-12	12	+0.050 +0.160	14	20	12	1
104FM-1214-17	12		14	20	17	1
104FM-1216-10	12		16	22	10	2
104FM-1216-20	12		16	22	20	2
104FM-1218-08	12		18	24	8	3
104FM-1218-10	12		18	22	10	3
104FM-1218-12	12		18	24	12	3
104FM-1218-15	12		18	22	15	3
104FM-1218-20	12		18	22	20	3
104FM-1315-14	13		15	20	14	2
104FM-131624-08	13		16	24	8	2
104FM-1416-12	14		16	22	12	1
104FM-1416-17	14		16	22	17	1
104FM-1420-07	14		20	25	7	3
104FM-1420-10	14		20	25	10	3
104FM-1420-15	14	+0.050 +0.160	20	25	15	3
104FM-1420-20	14		20	25	20	3
104FM-1517-09	15		17	23	9	1
104FM-1517-12	15		17	23	12	1
104FM-1517-17	15		17	23	17	1
104FM-1521-10	15		21	27	10	3
104FM-1521-15	15		21	27	15	3
104FM-1521-20	15		21	27	20	3
104FM-1521-25	15		21	27	25	3
104FM-1618-08/02	16		18	28	8	2

104系列壁厚
且耐用

104系列·产品规格

简灵科技工程塑料轴承
High Wear Resistance. Cost Down.



轴套- S型(mm)

1 产品代码	2 d	d 公差	3 D1	D2	K L1	L2
		压入 H7 孔后		h13	h13	-0.14
104FM-1618-12	16	+0.050 +0.160	18	24	12	1
104FM-1618-17	16		18	24	17	1
104FM-1622-12	16		22	28	12	3
104FM-1622-15	16		22	28	15	3
104FM-1622-20	16		22	28	20	3
104FM-1622-25	16		22	28	25	3
104FM-1820-12	18		20	26	12	1
104FM-1820-17	18		20	26	17	1
104FM-1820-22	18		20	26	22	1
104FM-182426-078	18		24	26	7.8	3
104FM-1824-08	18		24	30	8	3
104FM-1824-12	18		24	30	12	3
104FM-1824-18	18		24	30	18	3
104FM-1824-20	18		24	30	20	3
104FM-1824-30	18		24	30	30	3
104FM-192427-12	19	+0.065 +0.195	24	27	12	2
104FM-2023-11	20		23	30	11.5	1.5
104FM-2023-16	20		23	30	16.5	1.5
104FM-2023-21	20		23	30	21.5	1.5
104FM-202628-12	20		26	28	12	3
104FM-2026-15	20		26	32	15	3
104FM-2026-20	20		26	32	20	3
104FM-2026-30	20		26	32	30	3
104FM-2228-15	22		28	34	15	3
104FM-2228-20	22		28	34	20	3
104FM-2228-30	22		28	34	30	3
104FM-2430-15	24		30	36	15	3
104FM-2430-20	24		30	36	20	3
104FM-2430-30	24		30	36	30	3

1 产品代码	2d	d 公差		3D1	D2		4 L1	L2
		压入 H7 孔后			h13	h13		
104FM-2528-11	25	+0.065 +0.195		28	35	11.5	1.5	
104FM-2528-16	25			28	35	16.5	1.5	
104FM-2528-21	25			28	35	21.5	1.5	
104FM-2532-12	25			32	38	12	4	
104FM-2532-15	25			32	38	15	4	
104FM-2532-20	25			32	38	20	4	
104FM-2532-30	25			32	38	30	4	
104FM-2532-40	25			32	38	40	4	
104FM-2734-20	27			34	40	20	4	
104FM-2734-30	27			34	40	30	4	
104FM-2734-40	27			34	40	40	4	
104FM-2836-20	28			36	42	20	4	
104FM-2836-30	28			36	42	30	4	
104FM-2836-40	28			36	42	40	4	
104FM-3034-16	30			34	42	16	2	
104FM-3034-26	30		+0.080 +0.240		34	42	26	2
104FM-3035-20	30			35	44	20	4	
104FM-3038-20	30			38	44	20	4	
104FM-3038-30	30			38	44	30	4	
104FM-3038-40	30			38	44	40	4	
104FM-3240-20	32			40	46	20	4	
104FM-3240-30	32			40	46	30	4	
104FM-3240-40	32			40	46	40	4	
104FM-3539-16	35			39	47	16	2	
104FM-3539-26	35			39	47	26	2	
104FM-4044-30	40			44	52	30	2	
104FM-4044-40	40			44	52	40	2	
104FM-4550-50	45		50	58	50	2		

104系列壁厚
且耐用