

SIMART 简灵科技



耐高负载

重载摆动

免维护


109系列
坚固耐用

1

109系列·产品规格

简灵科技工程塑料轴承
High Wear Resistance. Cost Down.

轴套- S型(mm)



倒角f和内径d的关系：

d	Φ1-6	Φ6-12	Φ12-30	Φ >30
f	0.3	0.5	0.8	1.2

注：“当产品壁厚小于1mm时，倒角为20°。
尺寸符合ISO 3547-1标准，且提供定制服务。

订购编号示例 1 产品代码 109SM-0405-04 2 内径d 04 3 外径D 05 4 长度L 04

1 产品代码	2 d	d 公差	3 D	4 L
		压入 H7 孔后		h13
109SM-0405-04	4	+0.020 +0.068	5.5	4
109SM-0405-06	4		5.5	6
109SM-0507-05	5		7	5
109SM-0507-10	5		7	10
109SM-0608-06	6		8	6
109SM-0608-08	6		8	8
109SM-0608-10	6	+0.025 +0.083	8	10
109SM-0810-08	8		10	8
109SM-0810-10	8		10	10
109SM-0810-12	8		10	12
109SM-1012-08	10		12	8
109SM-1012-10	10		12	10
109SM-1012-12	10		12	12
109SM-1012-15	10	+0.032 +0.102	12	15
109SM-1012-20	10		12	20
109SM-1214-10	12		14	10
109SM-1214-12	12		14	12
109SM-1214-15	12		14	15
109SM-1214-20	12		14	20
109SM-1315-10	13		15	10
109SM-1315-20	13		15	20
109SM-1416-15	14		16	15
109SM-1416-20	14		16	20
109SM-1416-25	14		16	25
109SM-1517-15	15		17	15
109SM-1517-20	15		17	20
109SM-1517-25	15		17	25
109SM-1618-15	16		18	15
109SM-1618-20	16		18	20
109SM-1618-25	16		18	25
109SM-1820-15	18	+0.040 +0.124	20	15
109SM-1820-20	18		20	20
109SM-1820-25	18		20	25
109SM-2023-10	20		23	10
109SM-2023-15	20		23	15
109SM-2023-20	20		23	20
109SM-2023-25	20		23	25
109SM-2023-30	20		23	30
109SM-2225-15	22		25	15
109SM-2225-20	22		25	20
109SM-2225-25	22		25	25

109系列·产品规格

简灵科技工程塑料轴承
High Wear Resistance. Cost Down.




1 产品代码	2 d	d 公差	3 D	4 L
		压入 H7 孔后		h13
109SM-2225-30	22	+0.040 +0.124	25	30
109SM-2427-15	24		27	15
109SM-2427-20	24		27	20
109SM-2427-25	24		27	25
109SM-2427-30	24		27	30
109SM-2528-15	25		28	15
109SM-2528-20	25		28	20
109SM-2528-25	25		28	25
109SM-2528-30	25		28	30
109SM-2832-30	28		32	30
109SM-3034-20	30		34	20
109SM-3034-25	30		34	25
109SM-3034-30	30		34	30
109SM-3034-40	30		34	40
109SM-3035-40	30		35	40
109SM-3236-20	32	+0.050 +0.150	36	20
109SM-3236-30	32		36	30
109SM-3236-40	32		36	40
109SM-3240-40	32		40	40
109SM-3539-20	35		39	20
109SM-3539-30	35		39	30
109SM-3539-40	35		39	40
109SM-3539-50	35		39	50
109SM-4044-20	40		44	20
109SM-4044-30	40		44	30
109SM-4044-40	40		44	40
109SM-4044-50	40		44	50
109SM-4550-20	45		50	20
109SM-4550-30	45		50	30
109SM-4550-40	45		50	40
109SM-4550-50	45		50	50
109SM-5055-20	50	+0.060 +0.180	55	20
109SM-5055-30	50		55	30
109SM-5055-40	50		55	40
109SM-5055-50	50		55	50
109SM-5055-60	50		55	60
109SM-6065-60	60		65	60
109SM-6570-60	65		70	60
109SM-7075-60	70		75	60
109SM-7580-40	75		80	40

109系列|坚固耐用

109系列·产品规格

简灵科技工程塑料轴承
High Wear Resistance. Cost Down.

法兰轴承- F型(mm)



倒角f和内径d的关系:

d	Φ1-6	Φ6-12	Φ12-30	Φ>30
f	0.3	0.5	0.8	1.2

注: "当产品壁厚小于1mm时, 倒角为20°。
尺寸符合ISO 3547-1标准, 且提供定制服务。

订购编号示例 1 产品代码 109FM-0507-05 2 内径d 05 3 外径D 07 4 长度L1 05

1 产品代码	2 d	d 公差	3 D1	D2	4 L1	L2
		压入 H7 孔后		d13	h13	-0.14
109FM-0507-05	5	+0.020 +0.068	7	11	5	1
109FM-0608-04	6		8	12	4	1
109FM-0608-06	6		8	12	6	1
109FM-0608-08	6		8	12	8	1
109FM-0810-03	8	+0.032 +0.102	10	15	3	1
109FM-0810-05	8		10	15	5.5	1
109FM-0810-07	8		10	15	7.5	1
109FM-0810-09	8		10	15	9.5	1
109FM-0810-10	8		10	15	10	1
109FM-1012-07	10		12	18	7	1
109FM-1012-09	10		12	18	9	1
109FM-1012-10	10		12	18	10	1
109FM-1012-12	10		12	18	12	1
109FM-1012-17	10		12	18	17	1
109FM-1214-07	12	+0.032 +0.102	14	20	7	1
109FM-1214-09	12		14	20	9	1
109FM-1214-12	12		14	20	12	1
109FM-1214-17	12		14	20	17	1
109FM-1416-05	14		16	22	5	1
109FM-1416-12	14		16	22	12	1
109FM-1416-17	14		16	22	17	1
109FM-1517-09	15		17	23	9	1
109FM-1517-12	15		17	23	12	1
109FM-1517-17	15		17	23	17	1
109FM-1618-12	16	+0.032 +0.102	18	24	12	1
109FM-1618-17	16		18	24	17	1
109FM-1820-12	18		20	26	12	1
109FM-1820-17	18		20	26	17	1
109FM-1820-22	18		20	26	22	1
109FM-2023-11	20	+0.040 +0.124	23	30	11.5	1.5
109FM-2023-12	20		23	30	12	1.5
109FM-2023-16	20		23	30	16.5	1.5
109FM-2023-21	20		23	30	21.5	1.5
109FM-2528-11	25		28	35	11.5	1.5
109FM-2528-16	25		28	35	16.5	1.5
109FM-2528-21	25		28	35	21.5	1.5
109FM-3034-16	30		34	42	16	2
109FM-3034-26	30		34	42	26	2
109FM-3034-37	30		34	42	37	2
109FM-3034-40	30		34	42	40	2

109系列坚固耐用

109系列·产品规格

简灵科技工程塑料轴承
High Wear Resistance. Cost Down.



1 产品代码	2 d	d 公差	3 D1	D2	4 L1	L2
		压入 H7 孔后		d13	h13	-0.14
109FM-3539-16	35	+0.050 +0.150	39	47	16	2
109FM-3539-26	35		39	47	26	2
109FM-3539-40	35		39	47	40	2
109FM-4044-30	40		44	52	30	2
109FM-4044-40	40		44	52	40	2
109FM-4550-50	45		50	58	50	2
109FM-5055-10	50		55	63	10	2
109FM-5055-50	50		55	63	50	2
109FM-6065-60	60		65	73	60	2
109FM-8085-100	80		85	93	100	2.5
109FM-100105125-90	100	+0.072 +0.212	105	125	90	2.5
109FM-120125145-90	120	+0.085 +0.245	125	145	90	2.5

109系列坚固耐用

草图

